

Features

- Measures AC/DC voltage and current, frequency, resistance, capacitance and temperature
- Built-in non-contact voltage detector and double molded plastic housing
- Diode check and continuity functions
- Relative and data hold functions
- Backlit LCD and low battery indicator
- Cat. III 600V safety rating
- Includes test leads, thermocouple wire probe (Type K) with attached adapter, and batteries

Specifications

AC/DC Voltage

Range: AC: 60, 600mV, 6, 60, 600V
DC: 60, 600mV, 6, 60, 600V

Accuracy: AC: 60, 600mV $\pm(0.5\% \text{ rdg.} + 2 \text{ dgt.})$
6, 60, 600V $\pm(0.7\% \text{ rdg.} + 3 \text{ dgt.})$
DC: 60, 600mV $\pm(1.0\% \text{ rdg.} + 2 \text{ dgt.})$
6, 60, 600V $\pm(0.8\% \text{ rdg.} + 3 \text{ dgt.})$

Resolution: AC: 0.1, 1, 10mV, 0.1, 1V
DC: 0.1, 1, 10mV, 0.1, 1V

AC/DC Current

Range: 600, 6000 μ A, 60, 600mA, 6, 10A

Accuracy: AC: 600, 6000 μ A/60mA, 600mA $\pm(1.0\% \text{ rdg.} + 3 \text{ dgt.})$
6, 10A $\pm(1.2\% \text{ rdg.} + 3 \text{ dgt.})$
DC: 600, 6000 μ A/60.00mA, 600.0mA $\pm(0.7\% \text{ rdg.} + 2 \text{ dgt.})$
6.000, 10.00A $\pm(1.0\% \text{ rdg.} + 3 \text{ dgt.})$

Resolution: 0.1, 1, 10 μ A, 0.1, 1, 10mA

Resistance

Range: 600 Ω , 6, 60, 600k Ω , 6, 60M Ω

Accuracy: 600 Ω : $\pm(1.0\% \text{ rdg.} + 2 \text{ dgt.})$
6, 60, 600k Ω : $\pm(0.8\% \text{ rdg.} + 2 \text{ dgt.})$
6M Ω : $\pm(1.2\% \text{ rdg.} + 3 \text{ dgt.})$
60M Ω : $\pm(1.5\% \text{ rdg.} + 5 \text{ dgt.})$

Resolution: 0.1, 1, 10, 100 Ω , 1, 10k Ω

Capacitance

Range: 9.999nF, 99.99nF to 999.9 μ F, 9.999 to 99.99mF

Accuracy: 9.999nF: Under REL ($\pm 4\% + 10 \text{ dgt.}$)
99.99nF to 999.9 μ F: $\pm(4.0\% \text{ rdg.} + 5 \text{ dgt.})$
9.999 to 99.99mF: $\pm(10\% \text{ rdg.} < 2\text{mF})$

Resolution: 1pF, 10pf to 0.1 μ F, 1 μ F to 10 μ F

Frequency

Range: 9.999Hz to 9.999MHz

Accuracy: $\pm(0.1\% \text{ rdg.} + 4 \text{ dgt.})$

Resolution: 0.001Hz to 0.001Mz

TECHNICAL DATA



Continued...

Temperature

Range: -40 to 1832°F (-40 to 1000°C)
 Accuracy: $\pm(2.5\% \text{ rdg.} + 5^\circ\text{F}) \pm(2.0\% \text{ rdg.} + 3^\circ\text{C})$
 Resolution: 1°F, 1°C

General Specifications

Range Selection: Autoranging/Manual
 True RMS: Yes
 Display: 6,000 count LCD Display
 Display Hold: Yes
 Max/Min: Yes
 Relative Mode: Yes
 Diode Test: Yes
 Backlit Display: Yes
 Continuity Check: Audible signal if resistance $\leq 10\Omega$
 Duty Cycle: Yes (0.1 - 99.9%)
 Non-Contact
 Voltage Detector: Yes
 Kick Stand: Yes
 Auto Power Off: Yes (after 15 minutes)
 Power Supply: 2 x AA Batteries
 Low Battery Indicator: Yes
 Fuse Protection: Yes
 Replaceable Test Leads: Yes
 Overvoltage Category: CAT. III 600V
 Product Certifications: CE
 Operating Temperature: 41 to 104°F (5 to 40°C)
 Storage Temperature: -4 to 140°F (-20 to 60°C)
 Dimensions: 6.9 x 3.2 x 1.9"
 (175 x 80 x 49mm)
 Weight: 13oz (370g)

TECHNICAL DATA



Model	Description
R5007	Digital Multimeter
R5900	Magnetic Hanging Strap
FC-300	Fused Test Lead Set
P-15	Weatherproof Plugs
CP-09	AC Current Adapter
AD-1	Thermocouple Adapter
TP-01	Type K Thermocouple Wire Probe
TL-88-1	Test Leads
LS-103	Air/Gas Thermocouple Probe
LS-104	Right Angle Thermocouple Surface Probe
LS-107	Immersion Thermocouple Probe
LS-109	Surface Thermocouple Probe
LS-134A	Needle Tip Thermocouple Probe
LS-139	Spring Loaded Surface Probe
CA-05A	Soft Carrying Case
R5007-NIST	Digital Multimeter & NIST