

### Features

- Simultaneous display of %RH, temperature and dew point or wet bulb
- Optional external probe (87P6) for contact/differential temperature measurement
- Max/Min/Avg readings
- Fast response
- Data Hold Function
- User selectable °F/°C
- Low battery indicator and auto shut-off
- Includes batteries

### Specifications

#### Temperature

Measuring Range: -4 to 158°F (-20 to 70°C)  
 Accuracy: ±1.0°F (0.6°C)  
 Resolution: 0.1°F/°C

#### Contact Temperature (Probe sold separately)

Measuring Range: -4 to 122°F (-20 to 50°C)  
 Accuracy: ±1.0°F (0.6°C)  
 Resolution: 0.1°F/°C

#### Dew Point

Measuring Range: -109 to 122°F (-78 to 50°C)  
 Accuracy: ±3%  
 Resolution: 0.1°F/°C

#### Wet Bulb

Measuring Range: -69 to 122°F (-21 to 50°C)  
 Accuracy: ±3%  
 Resolution: 0.1°F/°C

#### Humidity

Measuring Range: 0-100% RH  
 Accuracy: ±3% RH  
 Resolution: 0.1% RH

#### General Specifications

Display: LCD  
 Data Hold: Yes  
 Min: Yes  
 Max: Yes  
 Auto Shut-off: Yes (5 mins/off)  
 Low Battery Indicator: Yes  
 Power Supply: 2 AAA Batteries  
 Product Certifications: CE  
 Operating Temperature: -4 to 158°F (-20 to 70°C)  
 Storage Temperature: 14 to 140°F (-10 to 60°C)  
 Operating Humidity Range: 10-80%  
 Dimensions: 7 x 1.9 x 1" (179 x 48 x 25mm)  
 Weight: 3.3 oz (95g)

### TECHNICAL DATA



Model	Description
8706	Digital Psychrometer
87P6	External Temperature Probe
RHA-33	33% Humidity Calibration Standard
RHA-75	75% Humidity Calibration Standard
CA-52A	Soft Carrying Case
8706-NIST	Digital Psychrometer & NIST